

100-140 VERSA-LIFT WITH 9 COUNTERWEIGHT SLABS

Slab Weight (kg)
2134

Number of Slabs
9

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	46400	50800	55200	59500	63900
	900	39300	42900	46600	50300	54000
	1200	34000	37200	40400	43600	46800
	1500	30000	32800	35600	38400	41200
	1800	26800	29300	31900	34400	36900
	2100	24300	26500	28800	31100	33400

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	41500	45500	49600	53600	57600
	400	37100	40700	44400	48000	51600
	600	33600	36800	40100	43400	46700
	800	30600	33600	36600	39600	42600
	1000	28100	30900	33600	36400	39200
	1200	25900	28500	31100	33700	36200
	1400	24100	26500	28900	31300	33700
	1600	22500	24700	27000	29200	31500
	1800	21000	23100	25300	27400	29500
	2000	19800	21800	23700	25700	27700
	2200	18600	20500	22400	24300	26200
	2400	17600	19400	21200	23000	24800
	2600	16700	18400	20100	21800	23500
	2800	15800	17500	19100	20700	22400
3000	15100	16600	18200	19800	21300	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	37300	41100	44900	48800	52600
	600	32200	35500	38700	42000	45300
	900	28300	31200	34100	36900	39800
	1200	25200	27800	30400	32900	35500
	1500	22800	25100	27400	29700	32100
	1800	20700	22900	25000	27100	29200

*****All Load Capacities are rated with the mast vertical**

100-140 VERSA-LIFT WITH 8 COUNTERWEIGHT SLABS

Slab Weight (kg)
2134

Number of Slabs
8

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	43100	47200	51200	55200	59300
	900	36500	39900	43300	46700	50100
	1200	31600	34500	37500	40500	43400
	1500	27800	30500	33100	35700	38300
	1800	24900	27200	29600	31900	34200
	2100	22500	24600	26700	28900	31000

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	38400	42200	45900	49600	53400
	400	34400	37700	41100	44400	47800
	600	31000	34100	37100	40200	43200
	800	28300	31100	33900	36700	39500
	1000	26000	28500	31100	33700	36300
	1200	24000	26400	28700	31100	33500
	1400	22000	24500	26700	28900	31200
	1600	20700	22800	24900	27000	29100
	1800	19400	21400	23300	25300	27300
	2000	18200	20100	21900	23800	25600
	2200	17200	18900	20700	22400	24200
	2400	16200	17900	19600	21200	22900
	2600	15400	16900	18500	20100	21700
	2800	14600	16100	17600	19100	20600
3000	13900	15300	16800	18200	19700	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	34400	37900	41500	45000	48600
	600	29700	32700	35800	38800	41900
	900	26100	28700	31400	34100	36800
	1200	23300	25600	28000	30400	32800
	1500	21000	23100	25300	27500	29600
	1800	19100	21100	23000	25000	27000

*****All Load Capacities are rated with the mast vertical**

100-140 VERSA-LIFT WITH 7 COUNTERWEIGHT SLABS

Slab Weight (kg)
2134

Number of Slabs
7

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	39800	43500	47200	51000	54700
	900	33600	36800	39900	43100	46200
	1200	29100	31900	34600	37300	40100
	1500	25700	28100	30500	32900	35300
	1800	23000	25100	27300	29400	31600
	2100	20800	22700	24700	26600	28600

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	35300	38800	42200	45700	49100
	400	31600	34700	37800	40900	44000
	600	28500	31300	34200	37000	39800
	800	26000	28600	31100	33700	36300
	1000	23800	26200	28600	31000	33300
	1200	22000	24200	26400	28600	30800
	1400	20400	22500	24500	26600	28600
	1600	19000	20900	22900	24800	26700
	1800	17800	19600	21400	23200	25000
	2000	16700	18400	20100	21800	23500
	2200	15700	17300	19000	20600	22200
	2400	14800	16400	17900	19500	21000
	2600	14100	15500	17000	18500	19900
	2800	13300	14700	16100	17500	18900
3000	12700	14000	15400	16700	18000	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	31500	34800	38000	41300	44600
	600	27200	30000	32800	35600	38400
	900	23900	26300	28800	31300	33800
	1200	21300	23500	25700	27900	30100
	1500	19200	21200	23200	25200	27200
	1800	17500	19300	21100	22900	24800

*****All Load Capacities are rated with the mast vertical**

100-140 VERSA-LIFT WITH 6 COUNTERWEIGHT SLABS

Slab Weight (kg)
2134

Number of Slabs
6

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	36500	39900	43300	46700	50100
	900	30800	33700	36600	39500	42400
	1200	26700	29200	31700	34200	36700
	1500	23500	25800	28000	30200	32400
	1800	21100	23000	25000	27000	29000
	2100	19000	20800	22600	24400	26200

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	32300	35400	38600	41700	44900
	400	28800	31700	34500	37300	40200
	600	26000	28600	31200	33800	36300
	800	23700	26000	28400	30800	33100
	1000	21700	23900	26100	28200	30400
	1200	20000	22000	24100	26100	28100
	1400	18600	20500	22300	24200	26100
	1600	17300	19100	20800	22600	24400
	1800	16200	17800	19500	21200	22800
	2000	15200	16700	18300	19900	21400
	2200	14300	15800	17200	18700	20200
	2400	13500	14900	16300	17700	19100
	2600	12700	14100	15400	16800	18100
	2800	12100	13400	14600	15900	17200
3000	11500	12700	13900	15200	16400	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	28600	31600	34600	37600	40500
	600	24600	27200	29800	32400	35000
	900	21700	23900	26200	28500	30700
	1200	19300	21300	23400	25400	27400
	1500	17400	19300	21100	22900	24700
	1800	15900	17500	19200	20900	22500

*****All Load Capacities are rated with the mast vertical**

100-140 VERSA-LIFT WITH 5 COUNTERWEIGHT SLABS

Slab Weight (kg)
2134

Number of Slabs
5

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	33100	36200	39300	42400	45500
	900	28000	30600	33300	35900	38500
	1200	24300	26500	28800	31100	33400
	1500	21400	23400	25400	27400	29400
	1800	19100	20900	22700	24500	26300
	2100	17300	18900	20600	22200	23800

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	29200	32100	34900	37800	40700
	400	26100	28600	31200	33800	36400
	600	23500	25800	28200	30500	32900
	800	21400	23500	25700	27800	30000
	1000	19600	21600	23500	25500	27500
	1200	18100	19900	21700	23600	25400
	1400	16700	18400	20200	21900	23600
	1600	15600	17200	18800	20400	22000
	1800	14500	16100	17600	19100	20600
	2000	13600	15100	16500	17900	19300
	2200	12800	14200	15500	16900	18200
	2400	12100	13400	14700	15900	17200
	2600	11400	12700	13900	15100	16300
	2800	10800	12000	13200	14300	15500
3000	10300	11400	12500	13600	14700	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	25700	28400	31100	33800	36500
	600	22100	24500	26800	29200	31500
	900	19400	21500	23600	25600	27700
	1200	17300	19200	21000	22900	24700
	1500	15700	17300	19000	20600	22300
	1800	14300	15800	17300	18800	20300

*****All Load Capacities are rated with the mast vertical**

100-140 VERSA-LIFT WITH 4 COUNTERWEIGHT SLABS

Slab Weight (kg)
2134

Number of Slabs
4

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	29800	32600	35400	38200	41000
	900	25200	27600	29900	32300	34600
	1200	21800	23900	25900	28000	30000
	1500	19200	21000	22900	24700	26500
	1800	17200	18800	20400	22100	23700
	2100	15600	17000	18500	19900	21400

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	26100	28700	31300	33900	36400
	400	23300	25600	27900	30300	32600
	600	21000	23100	25200	27300	29400
	800	19100	21000	22900	24900	26800
	1000	17500	19200	21000	22800	24600
	1200	16100	17700	19400	21000	22700
	1400	14900	16400	18000	19500	21100
	1600	13800	15300	16700	18200	19600
	1800	12900	14300	15600	17000	18400
	2000	12100	13400	14700	16000	17200
	2200	11400	12600	13800	15000	16200
	2400	10700	11900	13000	14200	15300
	2600	10100	11200	12300	13400	14500
	2800	9600	10600	11700	12700	13800
3000	9100	10100	11100	12100	13100	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	22800	25200	27600	30100	32500
	600	19600	21700	23800	25900	28000
	900	17200	19100	20900	22800	24600
	1200	15400	17000	18700	20300	22000
	1500	13900	15400	16900	18300	19800
	1800	12600	14000	15400	16700	18100

*****All Load Capacities are rated with the mast vertical**

100-140 VERSA-LIFT WITH 3 COUNTERWEIGHT SLABS

Slab Weight (kg)
2134

Number of Slabs
3

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	26500	29000	31400	33900	36400
	900	22400	24500	26600	28700	30800
	1200	19400	21200	23000	24800	26700
	1500	17100	18700	20300	21900	23500
	1800	15300	16700	18200	19600	21000
	2100	13800	15100	16400	17700	19000

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	23000	25300	27600	29900	32200
	400	20500	22600	24600	26700	28800
	600	18500	20400	22200	24100	26000
	800	16800	18500	20200	21900	23600
	1000	15300	16900	18500	20100	21700
	1200	14100	15600	17100	18500	20000
	1400	13100	14400	15800	17200	18500
	1600	12100	13400	14700	16000	17300
	1800	11300	12500	13700	14900	16100
	2000	10600	11700	12900	14000	15100
	2200	9900	11000	12100	13200	14200
	2400	9300	10400	11400	12400	13400
	2600	8800	9800	10800	11700	12700
	2800	8300	9300	10200	11100	12100
3000	7900	8800	9700	10600	11500	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	19800	22000	24200	26400	28500
	600	17100	19000	20900	22700	24600
	900	15000	16700	18300	20000	21600
	1200	13400	14900	16300	17800	19300
	1500	12100	13400	14700	16100	17400
	1800	11000	12200	13400	14600	15900

*****All Load Capacities are rated with the mast vertical**

100-140 VERSA-LIFT WITH 2 COUNTERWEIGHT SLABS

Slab Weight (kg)
2134

Number of Slabs
2

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	23100	25300	27500	29600	31800
	900	19600	21400	23200	25100	26900
	1200	16900	18500	20100	21700	23300
	1500	14900	16300	17700	19100	20500
	1800	13400	14600	15900	17100	18400
	2100	12100	13200	14400	15500	16600

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	19900	22000	24000	26000	28000
	400	17800	19600	21400	23200	25000
	600	16000	17600	19200	20900	22500
	800	14500	16000	17500	19000	20500
	1000	13200	14600	16000	17400	18800
	1200	12100	13400	14700	16000	17300
	1400	11200	12400	13600	14800	16000
	1600	10400	11500	12600	13800	14900
	1800	9700	10700	11800	12900	13900
	2000	9100	10000	11000	12000	13000
	2200	8500	9400	10400	11300	12300
	2400	8000	8900	9800	10700	11600
	2600	7500	8400	9200	10100	10900
	2800	7100	7900	8700	9500	10300
3000	6700	7500	8300	9000	9800	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	16900	18800	20700	22600	24500
	600	14600	16200	17900	19500	21100
	900	12800	14300	15700	17100	18600
	1200	11400	12700	14000	15300	16600
	1500	10300	11500	12600	13800	15000
	1800	9400	10500	11500	12600	13600

*****All Load Capacities are rated with the mast vertical**

100-140 VERSA-LIFT WITH 1 COUNTERWEIGHT SLAB

Slab Weight (kg)
2134

Number of Slab
1

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	19800	21700	23500	25400	27200
	900	16700	18300	19900	21500	23000
	1200	14500	15900	17200	18600	19900
	1500	12800	14000	15200	16400	17600
	1800	11400	12500	13600	14700	15700
	2100	10400	11300	12300	13300	14200

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	16900	18600	20300	22000	23700
	400	15000	16500	18100	19600	21200
	600	13500	14900	16300	17700	19100
	800	12200	13500	14700	16000	17300
	1000	11100	12300	13500	14700	15800
	1200	10200	11300	12400	13500	14600
	1400	9400	10400	11400	12500	13500
	1600	8700	9600	10600	11600	12500
	1800	8100	9000	9900	10800	11700
	2000	7500	8400	9200	10100	10900
	2200	7000	7800	8600	9500	10300
	2400	6600	7400	8100	8900	9700
	2600	6200	6900	7700	8400	9100
	2800	5800	6500	7200	7900	8600
3000	5500	6200	6800	7500	8200	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	14000	15600	17300	18900	20500
	600	12100	13500	14900	16300	17700
	900	10600	11800	13100	14300	15500
	1200	9500	10600	11700	12800	13900
	1500	8500	9500	10500	11500	12500
	1800	7800	8700	9600	10500	11400

*****All Load Capacities are rated with the mast vertical**

100-140 VERSA-LIFT WITH 0 COUNTERWEIGHT SLABS

Slab Weight (kg)
2134

Number of Slabs
0

Standard Wheel Base (mm)
3200

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	600	16500	18000	19600	21100	22700
	900	13900	15200	16500	17900	19200
	1200	12100	13200	14300	15500	16600
	1500	10600	11600	12600	13600	14600
	1800	9500	10400	11300	12200	13100
	2100	8600	9400	10200	11000	11800

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	200	13800	15200	16600	18100	19500
	400	12200	13500	14800	16100	17400
	600	10900	12100	13300	14400	15600
	800	9900	10900	12000	13100	14100
	1000	9000	10000	10900	11900	12900
	1200	8200	9100	10000	11000	11900
	1400	7500	8400	9200	10100	11000
	1600	7000	7800	8600	9400	10200
	1800	6400	7200	8000	8700	9500
	2000	6000	6700	7400	8100	8800
	2200	5600	6300	6900	7600	8300
	2400	5200	5900	6500	7100	7800
	2600	4900	5500	6100	6700	7300
	2800	4600	5200	5700	6300	6900
3000	4300	4900	5400	6000	6500	

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	300	11100	12500	13800	15200	16500
	600	9600	10700	11900	13100	14200
	900	8400	9400	10500	11500	12500
	1200	7500	8400	9300	10200	11200
	1500	6800	7600	8400	9200	10100
	1800	6200	6900	7700	8400	9200

*****All Load Capacities are rated with the mast vertical**